



Canyon 326 Main Specifications

Beam Amidships	10'9" (3.28 m)
Center Line Length w/o Engines	31'2" (9.50 m) (swim platforms not included)
LOA w/Swim Platforms	33'1" (10.08 m)
Bridge Clearance	9'5" (2.87 m)
Cockpit Depth	26" (0.66 m)
Hull Draft	24" (0.61 m)
Transom Deadrise	20 degrees (SeaV [®] progression)
Maximum HP	700 (522 kW)
Fuel Capacity - Standard	327 gal. (1238 l)
Weight w/o Engines	8500 lb. (3856 kg)

Canyon 326 Features & Options

STANDARD FEATURES

Safety

- 2 automatic bilge pumps (total 2600 GPH) (9842 LPH)
- Basic flotation
- Bow grab rail - low profile 316 grade stainless steel
- Cockpit toe rails
- Composite stringer system & transom - water impervious

Cockpit & Deck

- 100% hand laid hull & deck
- Anchor windlass w/remote switches at helm & windlass
- Batteries (4) w/battery select switches (one per engine) & charger system (1)
- Casting platform insert w/cushion
- Cleats - flush mount (pull up)
- Cockpit bolsters

- Fire extinguisher holder
- Nonskid fiberglass liner
- Self-bailing cockpit w/cockpit drains (4)
- Stainless steel through-hull fittings
- Hydraulic trim tabs w/indicator & retractor
- International lighting
- Livewell - 32 gal. (121 l) aft raw water livewell w/light, full column distribution inlet & ob drain (1100 GPH pump) (4164 LPH)
- Rod holders - bow (4), cockpit (4), transom (1)
- Rod storage racks - horizontal (3)
- Rubrail - high density PVC w/stainless steel insert

Cockpit side door - port w/boarding ladder

Cockpit freshwater shower (recessed)

Cockpit lights - blue LED

Cutting board

Deck hardware - 316 grade stainless steel through-bolted

Dockside power w/galvanic isolator

Drink holders - stainless steel (11)

Engine flush system w/hose attachment aft (one per engine)

Fish box - 180-qt. (170.3 l) port & starboard insulated fish box w/ob drain (2)

Fish box - 318-qt. (300.9 l) aft insulated fish box w/light & ob drain

Forward bolsters

Console

Accessory outlet - 5V duplex USB port

Accessory outlet - 12V

Compass

Console grab rails

Console ventilator

Door - lockable acrylic console door

Drink holders - stainless steel (3)

Factory engine pre-rigging

Flush mount electronics area

Footrest - molded console footrest

Deluxe Lean Bar

Footrests - fold down (2)

Livewell - 38-gallon (144 l) insulated raw water livewell w/light, full column distribution inlet & ob drain (1100 GPH pump) (4164 LPH)

Rigging station - freshwater sink w/faucet

Seating - foldaway aft bench seat w/cushion

Seating - port & starboard bow seating w/forward facing foldaway bolstered backrest (2)

Stereo - Deluxe stereo system w/amplifier & subwoofer

Stern eyes - 316 grade stainless steel

Storage - forward anchor locker w/rode storage

Storage - transom tackle storage compartment

Swim platforms - aft port & starboard extensions w/starboard ladder

Transom door - fiberglass

Washdown - freshwater (2)

Washdown - pressurized raw water (forward & aft) w/hose

Water tank - 30-gallon (113.6 l) freshwater

Head - lockable console w/lighting, sink, bulk storage, VacuFlush® head w/freshwater supply, 10-gallon (38 l) holding tank, overboard discharge & deck pump out & composite cherry & holly sole

Rod storage - vertical (4)

Seating - molded forward console seat w/cushion

Steering - Helm Master® EX w/Full Maneuverability

Steering wheel - 316 grade stainless steel w/knob

T-top w/painted aluminum frame, radio box, storage net, tri-colored (red, blue, white) LED recessed lights (4), fore/aft spreader lights, rod holders (4), radar flat & outrigger plates

Window - tinted frameless glass

Windshield - scratch resistant acrylic integrated w/T-top

Windshield wiper w/washer

Seating - lean bar mounted Command Elite helm chairs (3) horizontally adjustable w/deluxe cushioning & flip-up bolsters

Storage - lockable storage drawers

Storage - lockable w/tackle trays

Rod holders (4)

Storage - trash bin

OPTIONAL FEATURES

Options

Bow thruster

Cockpit step - starboard

CE certification package (European Conformity)

Hull color - Celestial Blue, Coastal Fog, Ocean Mist, or Sea Glass gelcoat

Lighting - underwater blue LED (3)

Outrigger kit - 18-ft. (5.5 m) crank T-top mounted stainless steel outriggers w/carbon fiber poles

Ski pylon (in lieu of transom rod holder)

SureShade® electrically retractable cockpit shade with Sunbrella® canvas (oyster)

Table - fiberglass bow table

T-top color - underside of fiberglass T-top (requires matching gelcoat hull color option)

Canvas Options

Easy up bow shade (ivory mesh)

T-top side wing curtains (ivory)