Fisherman 180

18' Center Console



Fisherman 180 Main Specifications

Beam Amidships	7'5" (2.26 m)
Center Line Length w/o Engines	17'10" (5.44 m)
Bridge Clearance	5'7" (1.70 m)
Cockpit Depth	22" (0.56 m)
Hull Draft	15" (0.38 m)
Transom Deadrise	19 degrees (SeaV ^{2®} progression)
Maximum HP	150 (112 kW)
Fuel Capacity - Standard	54 gal. (204 l)
Passenger Capacity	7
Weight w/o Engines	2150 lb. (975 kg)

Fisherman 180 Features & Options

Composite stringer system & transom - water impervious

STANDARD FEATURES

Stainless steel through-hull fittings

Safety

Automatic bilge pump (1100 GPH) (4164 LPH)

Level flotation

Bow grab rail - low profile 316 grade stainless steel Nonskid fiberglass liner

Cockpit toe rails Self-bailing cockpit w/cockpit drains (2)

Fire extinguisher holder

Cockpit & Deck

100% hand laid SeaV² hull & deck Rod holders - cockpit (4)

Batteries (2) w/battery select switch (1) Rod storage racks - horizontal (4)

Casting platform (raised) Rubrail - high density PVC w/stainless steel insert

Cleats Seating - aft seats (2)

Deck hardware - 316 grade stainless steel through-bolted Seating - bench seat w/reversible back

Drink holders - stainless steel (2)

Seating - forward platform cushions

Engine flush system w/hose attachment aft Stern eyes - 316 grade stainless steel

Factory engine pre-rigging

Storage - aft rigging compartments (2)

Fish box - 89-qt. (84.2 l) bow insulated box w/ob drain

Storage - forward anchor locker w/rode storage

Hydraulic trim tabs w/indicator & retractor

Swim platform - aft port side w/ladder

International lighting

Console

Accessory outlet - 12V Rod storage - vertical (4)

Compass Seating - forward console seat

Console grab rail Steering - hydraulic tilt

Drink holders - stainless steel (2) Steering wheel - 316 grade stainless steel w/knob

Flush mount electronics area Storage - lockable console storage

Footrest - molded console footrest Windshield - scratch resistant acrylic w/handrail

Livewell - 11-gallon (43 I) insulated raw water livewell w/light & ob drain (800 GPH pump) (3028 LPH)

OPTIONAL FEATURES

Options

CE certification package (European Conformity) Ski pylon

Cockpit freshwater shower (recessed) w/10-gallon (38 l) water tank

Washdown - pressurized raw water w/hose

Hull color - Celestial Blue, Coastal Fog, Ocean Mist, or Sea Glass gelcoat

Canvas Options

Bimini top w/boot (black)