30' Walkaround Cabin



Marlin 300 Main Specifications

Beam Amidships	10'7" (3.23 m)
Center Line Length w/o Engines	30'6" (9.30 m)
Bridge Clearance	9'9" (2.97 m)
Cockpit Depth	29" (0.74 m)
Hull Draft	23" (0.58 m)
Transom Deadrise	19.5 degrees (SeaV2® progression)
Maximum HP	700 (522 kW)
Fuel Capacity - Standard	282 gal. (1067 I)
Weight w/o Engines	8221 lb. (3729 kg)

Marlin 300 Features & Options

Composite stringer system & transom - water impervious

STANDARD FEATURES

Safety

2 automatic bilge pumps (total 2600 GPH) (9842 LPH) Nonskid fiberglass liner

Basic flotation Nonskid recessed walkaround

Bow rail - 316 grade stainless steel Self-bailing cockpit w/cockpit drains (4)

Cockpit toe rails Stainless steel through-hull fittings

Cabin

Accessory outlet - 5V duplex USB port Rod storage - aft berth horizontal (4)

Berth - aft double berth Rod storage - forward horizontal (6)

Berth - forward vee berth Stereo system w/waterproof touch screen display, AWFM

tuner, Wi-Fi & Bluetooth® connectivity & remote unit; Carbon monoxide detector speakers w/LED lights - helm (2), cabin (2), cockpit (2)

Door - lockable w/screen & companionway hatch Storage - galley cabinets & counter

Forward hatch - low profile acrylic hatch w/screen & shade Storage - under berth compartments

Galley - port galley w/sink, light & Corian® cutting board Storage nets

Head - enclosed head area w/sink, shower, lamp & VacuFlush® marine Stove - electric glass top

head w/freshwater supply, 10-gallon (38 I) holding tank, overboard	
discharge & deck pump out	Table - cherry
Lighting - dome (2)	Teak & holly sole
Lighting - reading (3)	Water heater - 6-gallon (22.7 I), 120V
Microwave oven	Water tank - 32-gallon (121.1 I) freshwater
Mirror	Windows - tinted frameless acrylic w/shade
Refrigerator - stainless steel	
Cockpit & Deck	
100% hand laid SeaV² hull & deck	International lighting
Accessory outlet - 5V duplex USB port	Livewell - 32-gallon (121.1 l) port insulated raw water livewell w/light, full column distribution inlet & ob drain (1100 GPH pump) (4164 LPH)
Accessory outlet - 12V	
Anchor windlass w/rode, line, and remote switches at helm & windlass	Rigging station - freshwater sink, insulated bait box w/ob drain & lockable drawers
Batteries (4) w/battery select switches (one per engine) & charger system (1)	Rod holders - cockpit (4)
Bow pulpit w/roller	Rod storage racks - horizontal (3)
Cleats	Rubrail - high density PVC w/stainless steel insert
Cockpit bolsters	Seating - Command Elite helm & companion chairs (2) horizontally & vertically adjustable w/deluxe cushioning & flip-up bolster
Cockpit freshwater shower w/hot & cold mixer	
Cockpit lights - blue LED	Seating - foldaway aft bench seat w/cushion
Cockpit side door - port w/boarding ladder	Seating - foredeck cushions
Companion grab rail	Seating - port livewell cushion
Deck hardware - 316 grade stainless steel through-bolted	Seating - starboard rigging station cushion
Dockside power w/galvanic isolator	Steering - Helm Master® EX w/Integrated Digital Electric
Drink holders - stainless steel (9)	Steering (does not include joystick)
Engine flush system w/hose attachment aft (one per engine)	Steering wheel - 316 grade stainless steel w/knob
Factory engine pre-rigging	Stern eyes - 316 grade stainless steel
Fighting chair reinforcement	Storage - aft deck lift out box
Fish box - 290-qt. (274.4 l) aft insulated fish box w/light & ob drain	Storage - forward anchor locker w/rode storage
Flush mount electronics area	Storage - lockable storage under helm & companion seats
Footrests - helm & companion (fold down)	Storage - under step compartment
Freshwater level indicator	Transducer mounting flats
	Transom door - fiberglass

Hardtop w/painted aluminum frame, radio box, storage nets, spreader lights, side mounted rod holders (4), outrigger plates & drop, front & side curtains (ivory)

Fuel capacity - 282 gallons (141-gallon tank, 141-gallon tank) (1067 I)

Hydraulic trim tabs w/indicator & retractor

Integrated outboard mounting system w/swim platform & ladder

Washdown - freshwater

Washdown - pressurized raw water w/hose

Water tank - 32-gallon (121.1 I)

Windshield - tempered glass w/side vents

Windshield wipers w/starboard washer

OPTIONAL FEATURES

Options

Air conditioning - 8000 BTU in cabin

Bow thruster

CE certification package (European Conformity)

Generator - 5kW diesel, 12-gallon (45.4 I) fuel capacity

Hardtop color - underside of fiberglass hardtop (requires matching gelcoat hull color option)

Hull color - Celestial Blue, Coastal Fog, Ocean Mist, or Sea Glass gelcoat

International AC electrical conversion - 220V (50Hz)

Lighting - underwater blue LED (3)

Outrigger kit - 18-ft. (5.5 m) crank hardtop mounted stainless steel outriggers w/carbon fiber poles

Painted hardtop top mounted rod holders (6)

Rod storage - folding cabin rack (4)

Seating - companion bench seat (replaces Command Elite companion chair)

Steering - Helm Master® EX w/Full Maneuverability

TV - 19" LED flat screen w/HDMI inlet